



# Contactspray

## Product description

Contactspray is a universal spray for the cleaning and maintenance of electric contact areas.

## Properties

- Rust and corrosion-resistant
- Improves transmission
- Prevents loss of tension
- Reduces humidity
- Non corrosive
- Water-repellent
- In and outdoor use
- Aerosol can be used in any angle (360°)

## Applications

- Suitable for electric contact points such as switches, stop contacts, batteries, measuring tools, etc.
- Cleans and deoxidizes surfaces and improves the power transmission at electric contacts.
- Prevents moisture penetration which could result in disturbances. Also suitable for dehumidising of electric wirework and tools.
- Ideal for electric installations, appliances, stop contacts and light switches....



## Technical data

Base	Mixture based on mineral oil
Consistency	Liquid
Density	Ca. 0,81 g/ml
Viscosity	1 mPa.s
Acidity level	Neutral
Application temperature	+5°C → +35°C
Temperature resistance	-50°C → +190°C
Flashpoint	52°C
Volatile organic compounds (VOC)	84%
Solubility in water	Not soluble

## Substrates

- Substrate types  
All types of metals and plastics.

## Application method

- Application method  
Shake can well before use. Switch off electrical equipment before spraying the product. Switch electric installations back on when spray is evaporated.



# Contactspray

## Health- and Safety Recommendations

Dangerous. Respect the precautions for use.

In case of contact with eyes, wash immediately with plenty of water.

Use only in well-ventilated areas.

## Packaging/Logistics

Colour: Transparent

Packaging: 400 ml aerosol

Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.