

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Construction Sealant Easy

Revision: 11/01/2022

Page 1 from 3

Reference nr DOP: 231855

Unique identification code of the product type:

Soudal Construction Sealant Easy

Intended use or uses of the construction product:

Sealant for facade for interior and exterior application.

Construction product in accordance with applicable harmonized specifications:

EN 15651-1:2012: Type F - EXT-INT

System or systems of assessment and verification of consistency of performance of the construction product, as set out in Annex V:

System 3: for essential characteristics

System 3: for reaction to fire

Name and contact address of the manufacturer as required pursuant to Article 11(5):

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

The notified body:

GINGER CEBTP, NB 0074 has carried out Determination of Product Type under system 3.

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Construction Sealant Easy

Revision: 11/01/2022

Page 2 from 3

Declared Performance: EN 15651-1:2012

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	NPD	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elongation at break	≥ 25%	
Durability	Pass	

Conditioning:

Method B

Test substrate:

Aluminium

Mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx

Technical Product Manager
B-2300 Turnhout, Belgium, 11/01/2022

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 11/01/2022

Page 3 from 3



NB 0074

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

22

Reference nr DOP: 231855

EN 15651-1: 2012

Sealant for facade for interior and exterior application.

Soudal Construction Sealant Easy

EN 15651-1:2012: Type F - EXT-INT

Conditioning:

Method B

Substrate:

Aluminium

Mortar

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	NPD	EN 15651-1: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elongation at break	≥ 25%	
Durability	Pass	