

## dry lubricant spray

Revision: 18/03/2022

Page 1 from 1

### Technical data

Basis	Mixture based on PTFE and solvents
Consistency	Fluid
Application temperature	5 °C → 35 °C

\* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. \*\* This information relates to fully cured product.

### Product description

Very powerful silicone-free and mineral-oil-free lubricant with high resistance.

### Substrates

*Substrates:* metals, Wood, Plastics

### Properties

- Not staining on wood, metal or plastics
- Lubricates
- Protects
- Removes dirt and grease
- For in- and outdoor use
- Aerosol can be used in any angle (360°)
- Offers lasting wear protection.
- Does not contain silicones

### Application method

*Application method:* Shake can well before use. Spray a thin layer onto friction points or joints and allow to dry. Drying time for a thin application: approx. 1 – 2 mins. Drying time for a thicker application approx. 5 mins.

### Applications

- Suitable for dry lubrication of friction points.
- Ideal for sliding roof and seat rails, sliding doors, window tilt mechanisms, locks, hinges, drawers, guide rails, ball bearings, electrical parts etc.
- Can be used for metals, plastic, rubber etc. under low and medium loads.
- Developed for applications where silicone-containing products are undesirable.
- Can be used as a lubricant and as a release agent, to be used on many different machines within the wood and plastic industry.

### Health- and Safety Recommendations

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water. Dangerous. Respect the precautions for use.

### Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

### Packaging

*Colour:* colourless

*Packaging:* 400 ml aerosol

### Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.