

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Parquet Sealant

Revision: 10/05/2023

Page 1 from 6

Reference nr DOP: 230062

Unique identification code of the product type:

Soudal Parquet Sealant

Intended use or uses of the construction product:

Sealant for facade for interior and exterior application.

Name and contact address of the manufacturer as required pursuant to Article 11(5):

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

Authorised representative:

-

System or systems of assessment and verification of consistency of performance of the construction product, as set out in Annex V:

System 3: for essential characteristics

System 3: for reaction to fire

Construction product in accordance with applicable harmonized specifications:

EN 15651-1:2012: Type F - EXT-INT: CLASS 12.5P

The notified body:

GINGER CEBTP, NB 0074 has carried out Determination of Product Type under system 3.

Declared Performance: EN 15651-1:2012

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	Class E	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 30%	
Elongation at break	≥ 25%	
Tensile properties at break after water immersion	≥ 100%	
Durability	Pass	

Conditioning:

Method A


Test substrate:

Aluminium

Mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx

Technical Product Manager
B-2300 Turnhout, Belgium, 10/05/2023

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Parquet Sealant

Revision: 10/05/2023

Page 3 from 6



NB 0074

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

14

Reference nr DOP: 230062

EN 15651-1: 2012

Sealant for facade for interior and exterior application.

Soudal Parquet Sealant

EN 15651-1:2012: Type F - EXT-INT: CLASS 12.5P

Conditioning:
Method A
Substrate:
Aluminium
Mortar

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 30%	
Elongation at break	≥ 25%	
Tensile properties at break after water immersion	≥ 100%	
Durability	Pass	

UK Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Parquet Sealant

Revision: 10/05/2023

Page 4 from 6

UK DoP Ref Nr.: 230062UK

Unique identification code of the product type:

Soudal Parquet Sealant

Intended use or uses of the construction product:

Sealant for facade for interior and exterior application.

Name and contact address of the manufacturer as required pursuant to Article 11(5):

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

Authorised representative:

Soudal UK, Soudal House, Unit 1, Centurion Way, Centurion Park, B77 5PN Tamworth, United Kingdom

System or systems of assessment and verification of consistency of performance of the construction product, as set out in Annex V:

System 3: for essential characteristics

System 3: for reaction to fire

Construction product in accordance with applicable harmonized specifications:

BS EN 15651-1:2012: Type F-EXT-INT: CLASS 12.5P

UKAB:

4ward Testing, AB 2538, has carried out Determination of the Product Type under AVCP system 3.

Declared Performance: BS EN 15651-1:2012

Reaction to fire	Class E	BS EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Elongation at break	NPD	
Tens prop at break water immersion	NPD	
Durability	Pass	

Conditioning:

Method A


Test substrate:

Aluminium

Mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx

Technical Product Manager
B-2300 Turnhout, Belgium, 10/05/2023

UKCA marking

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Parquet Sealant

Revision: 10/05/2023

Page 6 from 6

**UK
CA**

AB 2538

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

21

UK DoP Ref Nr.: 230062UK

BS EN 15651-1:2012

Sealant for facade for interior and exterior application.

Soudal Parquet Sealant

BS EN 15651-1:2012: Type F-EXT-INT: CLASS 12.5P

Conditioning:

Method A

Substrate:

Aluminium

Mortar

Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Elongation at break	NPD	
Tens prop at break water immersion	NPD	
Durability	Pass	