

# Compressed air

Revision: 21/12/2022

Page 1 from 1

## Technical data

Consistency	Gaseous
Application temperature	5 °C → 35 °C

\* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. \*\* This information relates to fully cured product.

## Product description

High-pressure gas spray.

of gas nests via spark discharge.

## Properties

- Cleans
- Contact-free cleaning
- Not staining

## Health- and Safety Recommendations

Take the usual labour hygiene into account. Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water.

Dangerous. Respect the precautions for use.

## Applications

- To use wherever dust has to be removed without making physical contact with the object or surface.
- Developed for cleaning electronic equipment, optical equipment and lenses, precision clockwork, medical devices, measuring devices and any other sensitive surface.
- Allows dry, contact-free cleaning.

## Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

## Packaging

*Packaging:* 400 ml aerosol

## Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

## Substrates

*Substrates:* Electrical and optical equipment

## Application method

*Application method:* Ensure that electrical equipment is fully powered down prior to cleaning. Hold the can strictly upright. Do not shake the can before use. Press spray top in short intervals as required. When cleaning electrical devices, ensure that an adequate amount of time is allowed for aeration prior to restoring power, to avoid possible deflagration

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.